# KIA (EU) SOUL PS SOUL 1.6 MPI (2014-2016)



PRODUCT RECOMMENDATION 1 Duranza ECO 5W-20 Presteza MSP 5W-30 Duranza LSP 5W-30  Change every 15000 km/ 12 months  USE  Alternative (acceptable) PRODUCT RECOMMENDATION 2 Duranza LSP 5W-30  Change every 15000 km/ 12 months  Duranza ECO 5W-20 Duranza LSP 5W-30  Change every 15000 km/ 12 months  USE  CLIMATE Moderate PRODUCT RECOMMENDATION 2 Duranza LSP 5W-30  Change every 15000 km/ 12 months  USE  Alternative, severe PRODUCT RECOMMENDATION 1 Duranza ECO 5W-20 Duranza LSP 5W-30  Change every 7500 km/ 6 months  USE  CLIMATE Moderate PRODUCT RECOMMENDATION 2 Duranza LSP 5W-30  Change every 7500 km/ 6 months  USE  CLIMATE Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 1 Duranza ECO 5W-20  Change every 7500 km/ 6 months  USE  CLIMATE Moderate  PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRESTEZA MSP 5W-30  Duranza LSP 5W-30  CHANGE  CLIMATE Moderate  PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 DURANZA LSP 5W-30  CLIMATE Moderate  CLIMATE Moderate  SP Matic 4036  USE  CLIMATE Moderate	USE		CLIMATE
Duranza ECO 5W-20  Change every 15000 km/ 12 months  USE  Alternative (acceptable)  PRODUCT RECOMMENDATION 1  Duranza LSP 5W-30  Change every 15000 km/ 12 months  USE  Alternative, Severe  PRODUCT RECOMMENDATION 2  Duranza LSP 5W-30  Change every 15000 km/ 12 months  USE  Alternative, Severe  PRODUCT RECOMMENDATION 2  Duranza LSP 5W-30  Duranza ECO 5W-20  Duranza LSP 5W-30  Change every 7500 km/ 6 months  USE  CLIMATE  Moderate  PRODUCT RECOMMENDATION 2  Duranza LSP 5W-30  Specialsynth MSP 5W-40  Change every 7500 km/ 6 months  USE  Preferred, severe  PRODUCT RECOMMENDATION 2  PRODUCT RECOMMENDATION 3  Duranza LSP 5W-30  Change every 7500 km/ 6 months  TRANSAXLE AUTOMATIC A6GF1 6/1  Capacity: 7,3 liter  USE  Normal  Moderate  Moderate  Moderate  CLIMATE  Moderate  Moderate  PRODUCT RECOMMENDATION 1  SP Matic 4036	Preferred		Moderate
Change every 15000 km/ 12 months  USE  Alternative (acceptable)  PRODUCT RECOMMENDATION 1  Duranza ECO 5W-20  Duranza LSP 5W-30  Duranza LSP 5W-30  Specialsynth MSP 5W-40  Change every 15000 km/ 12 months  USE  Alternative, severe  PRODUCT RECOMMENDATION 2  PRODUCT RECOMMENDATION 2  PRODUCT RECOMMENDATION 2  PRODUCT RECOMMENDATION 2  PRODUCT RECOMMENDATION 3  Specialsynth MSP 5W-40  Change every 7500 km/ 6 months  USE  Preferred, severe  PRODUCT RECOMMENDATION 2  PRODUCT RECOMMENDATION 2  PRODUCT RECOMMENDATION 3  Specialsynth MSP 5W-40  Change every 7500 km/ 6 months  USE  Presteza MSP 5W-30  Duranza LSP 5W-30  Duranza LSP 5W-30  Change every 7500 km/ 6 months  TRANSAXLE AUTOMATIC A6GF1 6/1 Capacity: 7.3 liter  USE  Normal  PRODUCT RECOMMENDATION 1  SP Matic 4036  USE  CLIMATE  Moderate  CLIMATE  Moderate	PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Alternative (acceptable)  PRODUCT RECOMMENDATION 1  PRODUCT RECOMMENDATION 2  Duranza LSP 5W-30  Specialsynth MSP 5W-40  Change every 15000 km/ 12 months  USE  Alternative, severe  PRODUCT RECOMMENDATION 2  Duranza LSP 5W-30  Specialsynth MSP 5W-40  Change every 7500 km/ 6 months  USE  Preferred, severe  PRODUCT RECOMMENDATION 2  PRESTEZA MSP 5W-30  Change every 7500 km/ 6 months  TRANSAXLE AUTOMATIC A6GF1 6/1  Capacity: 7,3 liter  USE  Normal  PRODUCT RECOMMENDATION 1  SP Matic 4036  CLIMATE  Moderate	Duranza ECO 5W-20	Presteza MSP 5W-30	Duranza LSP 5W-30
Alternative (acceptable)  PRODUCT RECOMMENDATION 1  PRODUCT RECOMMENDATION 2  Duranza LSP 5W-30  Specialsynth MSP 5W-40  Change every 15000 km/ 12 months  USE  Alternative, severe  PRODUCT RECOMMENDATION 2  Duranza LSP 5W-30  Specialsynth MSP 5W-40  Change every 7500 km/ 6 months  USE  Preferred, severe  PRODUCT RECOMMENDATION 2  PRESTEZA MSP 5W-30  Change every 7500 km/ 6 months  TRANSAXLE AUTOMATIC A6GF1 6/1  Capacity: 7,3 liter  USE  Normal  PRODUCT RECOMMENDATION 1  SP Matic 4036  CLIMATE  Moderate	Change every 15000 km/ 12 month	ns .	
PRODUCT RECOMMENDATION 1 Duranza ECO 5W-20 Duranza LSP 5W-30 Specialsynth MSP 5W-40 Change every 15000 km/ 12 months  USE Alternative, severe PRODUCT RECOMMENDATION 1 Duranza ECO 5W-20 Duranza LSP 5W-30 Specialsynth MSP 5W-40 Change every 7500 km/ 6 months  USE CLIMATE Moderate PRODUCT RECOMMENDATION 2 Duranza LSP 5W-30 Specialsynth MSP 5W-40 Change every 7500 km/ 6 months  USE Preferred, severe PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 2 Presteza MSP 5W-30 Duranza LSP 5W-30  Change every 7500 km/ 6 months  TRANSAXLE AUTOMATIC A6GF1 6/1 Capacity: 7,3 liter  USE Normal PRODUCT RECOMMENDATION 1 SP Matic 4036  CLIMATE Moderate  CLIMATE Moderate	USE		
Duranza ECO 5W-20  Change every 15000 km/ 12 months  USE  Alternative, severe  PRODUCT RECOMMENDATION 1  Duranza ECO 5W-20  Change every 7500 km/ 6 months  USE  PRODUCT RECOMMENDATION 2  Duranza LSP 5W-30  CLIMATE  Moderate  PRODUCT RECOMMENDATION 2  Duranza LSP 5W-30  CLIMATE  Moderate  PRODUCT RECOMMENDATION 2  PRODUCT RECOMMENDATION 2  PRODUCT RECOMMENDATION 2  PRODUCT RECOMMENDATION 3  Duranza ECO 5W-20  Presteza MSP 5W-30  Change every 7500 km/ 6 months  TRANSAXLE AUTOMATIC A6GF1 6/1  Capacity: 7,3 liter  USE  Normal  PRODUCT RECOMMENDATION 1  SP Matic 4036  CLIMATE  Moderate  CLIMATE  Moderate	Alternative (acceptable)		Moderate
Change every 15000 km/ 12 months  USE Alternative, severe  PRODUCT RECOMMENDATION 1 Duranza ECO 5W-20 Duranza LSP 5W-30 Specialsynth MSP 5W-40  Change every 7500 km/ 6 months  USE PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 2 Preferred, severe  PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Duranza ECO 5W-20 Presteza MSP 5W-30 Duranza LSP 5W-30  Change every 7500 km/ 6 months  TRANSAXLE AUTOMATIC A6GF1 6/1 Capacity: 7,3 liter  USE Normal PRODUCT RECOMMENDATION 1 SP Matic 4036  CLIMATE Moderate  CLIMATE Moderate	PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Alternative, severe  Moderate  PRODUCT RECOMMENDATION 1  Duranza ECO 5W-20  Duranza LSP 5W-30  Change every 7500 km/ 6 months  USE  Preferred, severe  PRODUCT RECOMMENDATION 1  PRODUCT RECOMMENDATION 2  PRODUCT RECOMMENDATION 1  PRODUCT RECOMMENDATION 2  PRODUCT RECOMMENDATION 2  PRODUCT RECOMMENDATION 3  Duranza ECO 5W-20  Presteza MSP 5W-30  Duranza LSP 5W-30  Change every 7500 km/ 6 months  TRANSAXLE AUTOMATIC A6GF1 6/1  Capacity: 7,3 liter  USE  Normal  PRODUCT RECOMMENDATION 1  SP Matic 4036  CLIMATE  Moderate  CLIMATE  Moderate	Duranza ECO 5W-20	Duranza LSP 5W-30	Specialsynth MSP 5W-40
Alternative, severe  PRODUCT RECOMMENDATION 1 Duranza ECO 5W-20 Duranza LSP 5W-30 Specialsynth MSP 5W-40  Change every 7500 km/ 6 months  USE Preferred, severe PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Duranza ECO 5W-20 Presteza MSP 5W-30 Duranza LSP 5W-30  Change every 7500 km/ 6 months  TRANSAXLE AUTOMATIC A6GF1 6/1 Capacity: 7,3 liter  USE CLIMATE Moderate PRODUCT RECOMMENDATION 2 Presteza MSP 5W-30  CLIMATE Moderate  CLIMATE Moderate  PRODUCT RECOMMENDATION 3 Duranza LSP 5W-30  CLIMATE Moderate  PRODUCT RECOMMENDATION 1 SP Matic 4036  CLIMATE  Moderate	Change every 15000 km/ 12 month	NS .	
PRODUCT RECOMMENDATION 1 Duranza ECO 5W-20 Duranza LSP 5W-30 Specialsynth MSP 5W-40 Change every 7500 km/ 6 months  USE Preferred, severe PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 2 Presteza MSP 5W-30 Duranza ECO 5W-20 Presteza MSP 5W-30 Duranza LSP 5W-30  Change every 7500 km/ 6 months  TRANSAXLE AUTOMATIC A6GF1 6/1 Capacity: 7,3 liter  USE CLIMATE Moderate  CLIMATE Moderate  PRODUCT RECOMMENDATION 1 SP Matic 4036  CLIMATE Moderate	USE		CLIMATE
Duranza ECO 5W-20  Change every 7500 km/ 6 months  USE  Preferred, severe  PRODUCT RECOMMENDATION 1  Duranza ECO 5W-20  Change every 7500 km/ 6 months  TRANSAXLE AUTOMATIC A6GF1 6/1 Capacity: 7,3 liter  USE  Normal  PRODUCT RECOMMENDATION 1  Duranza ECO 5W-20  Change every 7500 km/ 6 months  CLIMATE  Moderate  PRODUCT RECOMMENDATION 2  Duranza LSP 5W-30  CLIMATE  Moderate  PRODUCT RECOMMENDATION 1  SP Matic 4036  CLIMATE	Alternative, severe		Moderate
Change every 7500 km/ 6 months  USE Preferred, severe Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 Presteza MSP 5W-30  Change every 7500 km/ 6 months  TRANSAXLE AUTOMATIC A6GF1 6/1 Capacity: 7,3 liter  USE Normal PRODUCT RECOMMENDATION 1 SP Matic 4036  CLIMATE		PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
USE  Preferred, severe  PRODUCT RECOMMENDATION 1  Duranza ECO 5W-20  Presteza MSP 5W-30  Change every 7500 km/ 6 months  TRANSAXLE AUTOMATIC A6GF1 6/1 Capacity: 7,3 liter  USE  Normal  PRODUCT RECOMMENDATION 2  Presteza MSP 5W-30  Duranza LSP 5W-30  CLIMATE  Moderate  PRODUCT RECOMMENDATION 1  SP Matic 4036  CLIMATE	Duranza ECO 5W-20	Duranza LSP 5W-30	Specialsynth MSP 5W-40
Preferred, severe  PRODUCT RECOMMENDATION 1 Duranza ECO 5W-20 Presteza MSP 5W-30  Change every 7500 km/ 6 months  TRANSAXLE AUTOMATIC A6GF1 6/1 Capacity: 7,3 liter  USE CLIMATE  PRODUCT RECOMMENDATION 2 Duranza LSP 5W-30  CLIMATE  Moderate  PRODUCT RECOMMENDATION 1 SP Matic 4036  CLIMATE  CLIMATE  CLIMATE	Change every 7500 km/ 6 months		
PRODUCT RECOMMENDATION 1  Duranza ECO 5W-20  Presteza MSP 5W-30  Change every 7500 km/ 6 months  TRANSAXLE AUTOMATIC A6GF1 6/1 Capacity: 7,3 liter  USE  Normal  PRODUCT RECOMMENDATION 2  Duranza LSP 5W-30  CLIMATE  Moderate  PRODUCT RECOMMENDATION 1  SP Matic 4036	USE		CLIMATE
Duranza ECO 5W-20  Change every 7500 km/ 6 months  TRANSAXLE AUTOMATIC A6GF1 6/1 Capacity: 7,3 liter  USE  Normal  PRODUCT RECOMMENDATION 1  SP Matic 4036  USE  CLIMATE  CLIMATE  Moderate	Preferred, severe		Moderate
Change every 7500 km/ 6 months  TRANSAXLE AUTOMATIC A6GF1 6/1 Capacity: 7,3 liter  USE  Normal  PRODUCT RECOMMENDATION 1 SP Matic 4036  CLIMATE  CLIMATE  CLIMATE  CLIMATE	PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
TRANSAXLE AUTOMATIC A6GF1 6/1 Capacity: 7,3 liter  use	Duranza ECO 5W-20	Presteza MSP 5W-30	Duranza LSP 5W-30
Capacity: 7,3 liter  USE  Normal  PRODUCT RECOMMENDATION 1  SP Matic 4036  USE  CLIMATE  CLIMATE  CLIMATE	Change every 7500 km/ 6 months		
Capacity: 7,3 liter  USE  Normal  PRODUCT RECOMMENDATION 1  SP Matic 4036  USE  CLIMATE  CLIMATE  CLIMATE			
Normal Moderate  PRODUCT RECOMMENDATION 1  SP Matic 4036  USE CLIMATE		1 6/1	
PRODUCT RECOMMENDATION 1 SP Matic 4036  USE  CLIMATE	USE		CLIMATE
SP Matic 4036  USE  CLIMATE	Normal		Moderate
USE CLIMATE	PRODUCT RECOMMENDATION 1		
	SP Matic 4036		
Severe Moderate	USE		CLIMATE
	Severe		Moderate
	SP Matic 4036		

Change every 90000 km

## KIA (EU) SOUL PS SOUL 1.6 MPI (2014-2016)



TRANSAXLE MANUAL M6CF1 6/1 Capacity: 1,8-1,9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 1081		
Check every 48 months/ 60000 km		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 1081		
Check every 60000 km/ 48 months, chang	e every 120000 km	

HYDRAULIC BRAKE/CLUTCH SYSTEM Capacity: 0,7-0,8 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3		
Check every 15000 km/12 months ch	sange every 30000 km/24 months	'		

Check every 15000 km/12 months, change every 30000 km/24 months

COOLING SYSTEM Capacity: 5-5,2 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant SP 15+	Coolant SP 12		

Check every 30000 km/24 months, change every 30000 km/24 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Check every 60000 km/ 48 months, change every 210000 km/ 120 months

### AIRCONDITIONING COMPRESSOR

Capacity: 100-120 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

### KIA (EU) SOUL PS SOUL 1.6 MPI (2014-2016)



#### **AIRCONDITIONING SYSTEM** R-1234yf

Capacity: 525-575 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

#### **AIRCONDITIONING SYSTEM R-134a**

Capacity: 525-575 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.