

LANCIA THEMA THEMA 2.8 V6 (1984-1992)

**ENGINE 834E.146**

Capacity: 6,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Emperol 10W-40

PRODUCT RECOMMENDATION 2

Bi-Turbo 15W-40*Change every 10000 km/ 6 months***TRANSAXLE AUTOMATIC 3/1**

Capacity: 2,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

ATF Dexron II-D*Check every 1 months, change every 30000 km***TRANSAXLE MANUAL 5/1**

Capacity: 1,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

Gearlube GL-4 80W*Check every 20000 km, change every 40000 km/ 24 months***HYDRAULIC SYSTEM POWER STEERING/LEVELLING**

Capacity: 3,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

ATF Dexron II-D*Check every 1 months***HYDRAULIC BRAKE SYSTEM**

Capacity: 0,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4*Change every 40000 km/ 48 months*

LANCIA THEMA THEMA 2.8 V6 (1984-1992)**HYDRAULIC BRAKE SYSTEM ABS**

Capacity: 0,55 liter

USE		CLIMATE
Normal		Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

*Change every 40000 km/ 48 months***POWER STEERING**

Capacity: 0,95 liter

USE		CLIMATE
Normal		Moderate

PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

*Check every 1 months***COOLING SYSTEM**

Capacity: 6 liter

USE		CLIMATE
Normal		Moderate

PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		

Change every 60000 km/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.