## **LANCIA YPSILON YPSILON 1.2** (1996-2000)



ENGINE 840A3000 Capacity: 3,85 liter (Initial fill), Capacity: 3,5 liter (Service fill), Filter capacity: 0,4 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Duranza LSP 5W-30	Emperol Racing 10W-60	Asyntho 5W-30	

Change every 15000 km/ 12 months

TRANSAXLE AUTOMATIC 1/1 Capacity: 1,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4016		
Check every 500 km, change every 45000	km	

TRANSAXLE MANUAL 5/1 Capacity: 1,7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Syngear 75W-90
Check every 45000 km/ 36 months	, change every 120000 km	

TRANSAXLE MANUAL 6/1 Capacity: 1,9 liter		
use Normal		CLIMATE  Moderate
Nonna		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Syngear 75W-90

Check every 45000 km/36 months, change every 120000 km

HYDRAULIC BRAKE SYSTEM Capacity: 0,4 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		
Check every 500 km. change every 24	months		

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF

Change every 24 months

## **LANCIA YPSILON YPSILON 1.2** (1996-2000)



POWER STEERING Capacity: 0,7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
Check every 500 km		
COOLING SYSTEM Capacity: 4,67 liter, Capacity: 4,45 liter (+ a	airconditioning)	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		
Check every 500 km, change every 60000	km/ 48 months	
USE		CLIMATE
Severe		Moderate

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.