# LAND ROVER (EU) DEFENDER L316 DEFENDER 90 2.2 TD4 (110 KW) (2015-2015)



ENGINE ID4 Capacity: 7 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Duranza LSP 5W-30	
Change every 20000 km/ 12 months	
USE	CLIMATE
Severe	Moderate
PRODUCT RECOMMENDATION 1	
Duranza LSP 5W-30	
Change every 10000 km/ 6 months	

<b>DIFFERENTIAL FRONT</b> Capacity: 1,7 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube GL-5 80W-90	

<b>DIFFERENTIAL REAR</b> Capacity: 1,7 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube GL-5 80W-90	

SP Gear 1011	Syngear TDL 75W-90	Syngear 75W-90
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Normal		Moderate
USE		CLIMATE
RANSFERBOX LT230QRS apacity: 2,3 liter		CLIMATE

# LAND ROVER (EU) DEFENDER L316 DEFENDER 90 2.2 TD4 (110 KW) (2015-2015)



TRANSMISSION MANUAL MT82 6/1 Capacity: 2,4 liter (Dry fill), Capacity: 2,2 liter (Service fill)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

HYDRAULIC BRAKE SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-LV Super DOT 4	
Change every 40000 km/ 48 months	'

HYDRAULIC CLUTCH SYSTEM

USE

Normal

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

Check every 20000 km/ 12 months

POWER STEERING	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Fluid 3013	
Check every 20000 km/ 12 months	·

GREASE POINTS/NIPPLES PRO	PELLER SHAFT JOINTS	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

### LAND ROVER (EU) DEFENDER L316 DEFENDER 90 2.2 TD4 (110 KW) (2015-2015)



GREASE POINTS/NIPPLES PROPELLER SHAFT SLIDING JOINTS		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

#### **GREASE POINTS/NIPPLES SWIVEL PIN HOUSINGS**

Capacity: 0,35 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

COOLING SYSTEM Capacity: 1,2 liter (Expansion tank)	, Capacity: 2,3 liter (Radiator), Capacity: 11,	,5 liter (System)
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
Check every 20000 km/ 12 months	, change every 120 months	1

#### **AIRCONDITIONING COMPRESSOR**

We are unable to give a standard recommendation for this component. Please contact our service department.

### AIRCONDITIONING SYSTEM

Capacity: 575-625 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.