

LAND ROVER (EU) RANGE ROVER L322/LM

RANGE ROVER V8 4.2 SC (2005-2009)



ENGINE 428PS - AJV8 4.2 SC
Capacity: 7,7 liter, Capacity: 9,4 liter (Dry fill)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Duranza LSP 5W-30

Change every 24000 km/ 12 months

DIFFERENTIAL FRONT

Capacity: 0,75 liter, Capacity: 0,8 liter (Dry fill)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90

PRODUCT RECOMMENDATION 3

Syngear 75W-90

Check every 48000 km/ 24 months, change every 240000 km/ 120 months

DIFFERENTIAL REAR

Capacity: 1,14 liter, Capacity: 1,2 liter (Dry fill)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90

PRODUCT RECOMMENDATION 3

Syngear 75W-90

Change every 120000 km/ 12 months

DIFFERENTIAL REAR

Capacity: 1,55 liter, Capacity: 1,6 liter (Dry fill)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

SP Gear LS 1015

Change every 120000 km/ 12 months

TRANSFERBOX

Capacity: 1,5 liter (Dry fill)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

SP Matic 2072

Change every 120000 km/ 60 months

LAND ROVER (EU) RANGE ROVER L322/LM

RANGE ROVER V8 4.2 SC (2005-2009)

**TRANSMISSION AUTOMATIC ZF 6HP26 6/1**

Capacity: 9,5 liter

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| SP Matic 4026 | | |

HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

| USE | | CLIMATE |
|----------------------------------|---------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | |

*Change every 36 months***POWER STEERING**

Capacity: 1,6 liter

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| SP Fluid 3013 | | |

COOLING SYSTEM

Capacity: 16 liter

| USE | | CLIMATE |
|--------------------------|--------------------------|-------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Coolant SP 15+ | Coolant SP 12 | Coolant -38 Organic NF |

*Check every 48000 km/ 24 months, change every 240000 km/ 120 months***AIRCONDITIONING COMPRESSOR**

Capacity: 120 CM3 (with 2 zone airconditioning system), Capacity: 170 CM3 (with 4 zone airconditioning system)

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM

Capacity: 700 grams (with 2 zone airconditioning system), Capacity: 880 grams (with 4 zone airconditioning system)

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.