

LANDWIND CV9 CV9 1.6 JX6441A/JX6441LB

(2011 AND AFTER)

**ENGINE**

Capacity: 3,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Bi-Turbo 15W-40*Change every 5000 km*

USE

Severe

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Bi-Turbo 15W-40*Change every 5000 km/ 3 months***TRANSMISSION MANUAL 5/1**

Capacity: 2,3 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90**HYDRAULIC BRAKE SYSTEM**

Capacity: 0,6 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4*Change every 80000 km/ 48 months***POWER STEERING**

Capacity: 0-0 liter (Between min and max.)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

ATF Dexron II-D

LANDWIND CV9 CV9 1.6 JX6441A/JX6441LB (2011 AND AFTER)

**COOLING SYSTEM**

Capacity: 8 liter, Capacity: 1,5 liter (Reservoir)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		

Change every 80000 km/ 48 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.