

LEXUS (USA / CAN) GS S160 GS 300 (USA) (1999-1999)

**ENGINE 2JZ-GE**

Capacity: 5,4 liter (Service fill), Filter capacity: 0,3 liter

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Asyntho 5W-30 | | |

DIFFERENTIAL REAR

Capacity: 1,35 liter

| USE | | CLIMATE |
|-----------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Gearlube GL-5 80W-90 | | |

| USE | | CLIMATE |
|--------------------------|----------------------------|--------------------------|
| Normal | | Arctic |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| SP Gear 5015 | Gearlube RPC 75W-80 | SP Gear 1071 |

TRANSMISSION AUTOMATIC A650E 5/1

Capacity: 2,4 liter (Service fill)

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| SP Matic 4026 | | |

HYDRAULIC BRAKE SYSTEM

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Drauliquid DOT 3 | | |

POWER STEERING

| USE | | CLIMATE |
|--------------------------|--------------------------|--------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| SP Matic 2032 | ATF Almirol | ATF Dexron II-D |

LEXUS (USA / CAN) GS S160 GS 300 (USA) (1999-1999)

**COOLING SYSTEM**

Capacity: 7,7 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 12 EVO

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.