

LEXUS (USA / CAN) LS XF10 LS 400 (USA) (1990-1990)

**ENGINE 1UZ-FE**

Capacity: 6 liter (Dry fill), Capacity: 5 liter (Service fill), Filter capacity: 0,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Asyntho 5W-30*Change every 7500 miles/ 12 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Asyntho 5W-30*Change every 3750 miles/ 6 months***DIFFERENTIAL REAR**

Capacity: 1,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90*Check every 15000 miles/ 24 months*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

Gearlube RPC 75W-80

PRODUCT RECOMMENDATION 3

SP Gear 1071*Check every 15000 miles/ 24 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90*Change every 15000 miles/ 24 months*

USE	CLIMATE
Severe	Arctic

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

Gearlube RPC 75W-80

PRODUCT RECOMMENDATION 3

SP Gear 1071*Change every 15000 miles/ 24 months*

LEXUS (USA / CAN) LS XF10 LS 400 (USA) (1990-1990)



TRANSMISSION AUTOMATIC A341E 4/1
Capacity: 7,2 liter (Dry fill), Capacity: 1,6 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 4026		

Check every 15000 miles/ 24 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 4026		

Change every 15000 miles/ 24 months

HYDRAULIC BRAKE SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

Check every 15000 miles/ 24 months, change every 30000 miles/ 36 months

POWER STEERING

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

Check every 15000 miles/ 24 months

COOLING SYSTEM

Capacity: 10,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		

Change every 30000 miles/ 24 months

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		

Change every 45000 miles/ 36 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products.

LEXUS (USA / CAN) LS XF10 LS 400 (USA) (1990-1990)



Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.