

# LEXUS (USA / CAN) LS XF30 LS 430 (USA) (2003-2003)

**ENGINE 3UZ-FE**

Capacity: 5,1 liter (Service fill), Filter capacity: 0,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Duranza LSP 5W-30</b>	<b>Asyntho 5W-30</b>	

*Change every 7500 miles/ 6 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Duranza LSP 5W-30</b>	<b>Asyntho 5W-30</b>	

*Change every 5000 miles/ 4 months***DIFFERENTIAL REAR**

Capacity: 1,35 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Gearlube GL-5 80W-90</b>		

*Check every 15000 miles/ 12 months*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>SP Gear 5015</b>	<b>Gearlube RPC 75W-80</b>	<b>SP Gear 1071</b>

*Check every 15000 miles/ 12 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1		
<b>Gearlube GL-5 80W-90</b>		

*Change every 15000 miles/ 12 months*

USE	CLIMATE
Severe	Arctic

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>SP Gear 5015</b>	<b>Gearlube RPC 75W-80</b>	<b>SP Gear 1071</b>

*Change every 15000 miles/ 12 months*

# LEXUS (USA / CAN) LS XF30 LS 430 (USA) (2003-2003)


**TRANSMISSION AUTOMATIC A650E 5/1**

Capacity: 8,9 liter (Dry fill), Capacity: 1,8 liter (Service fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>SP Matic 4026</b>		

*Check every 30000 miles/ 24 months*

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
<b>SP Matic 4026</b>		

*Check every 30000 miles/ 24 months, change every 60000 miles/ 24 months*
**HYDRAULIC BRAKE SYSTEM ABS**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Drauliquid DOT 3</b>		

*Change every 30000 miles/ 24 months*
**POWER STEERING**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>SP Matic 2032</b>	<b>ATF Almirol</b>	<b>ATF Dexron II-D</b>

*Check every 15000 km/ 12 months*
**COOLING SYSTEM**

Capacity: 9,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant SP 12 EVO</b>		

*Change every 30000 miles/ 24 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.