LEXUS (USA / CAN) RX XU10 RX 300 FWD (USA) (1999-1999)



Capacity: 5,2 liter (Dry fill), Capacity: 4,7 liter (Service fill), Filter capacity: 0,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Asyntho 5W-30		
Change every 7500 miles/ 6 months		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
Asyntho 5W-30		
Change every 5000 miles/ 4 months		
TRANSAXLE AUTOMATIC U140E 4/1 Capacity: 3,1 liter (Service fill)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		
Check every 30000 miles/ 24 months		
USE		CLIMATE

Check every 30000 miles/24 months	, change every 60000 miles/ 48 months

YDRAULIC BRAKE SYSTEM		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
Check every 15000 miles/ 12 months, change every 30000 miles/ 24 months		

Severe

PRODUCT RECOMMENDATION 1

SP Matic 4026

Moderate

LEXUS (USA / CAN) RX XU10 RX 300 FWD (USA) (1999-1999)



Ohada ayan 45000 milada 40 manila			
SP Matic 2032	ATF Almirol	ATF Dexron II-D	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Normal		Moderate	
USE		CLIMATE	
POWER STEERING			

Check every 15000 miles/ 12 months

COOLING SYSTEM Capacity: 9 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Coolant SP 12 EVO		
Change every 30000 miles/ 24 months		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.