LEXUS (USA / CAN) RX XU30 RX 330 FWD (USA) (2004-2005)



ENGINE 3MZ-FE Capacity: 5,5 liter (Dry fill), Capacity: 4,7 liter (Service fill), Filter capacity: 0,2 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Asyntho 5W-30			
Channe over 5000 miles (C menthe			

Change every 5000 miles/ 6 months

TRANSAXLE AUTOMATIC U151E 5/1 Capacity: 8,8 liter (Dry fill), Capacity: 3,5 liter (Service fill)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
SP Matic 4026			
Check every 30000 miles/ 36 months			

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		
Charly avery 20000 miles/26 menths, change every 60000 miles/70 menths		

Check every 30000 miles/ 36 months, change every 60000 miles/ 72 months

HYDRAULIC BRAKE SYSTEM			
USE	CLIMATE		
Normal	Moderate		
PRODUCT RECOMMENDATION 1			
Drauliquid DOT 3			
Chaolic avant 15000 miles/ 18 months, abanga avant 20000 miles/ 26 months			

Check every 15000 miles/ 18 months, change every 30000 miles/ 36 months

POWER STEERING		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D
•• • • • • • • • • •		

Check every 15000 miles/ 18 months

LEXUS (USA / CAN) RX XU30 RX 330 FWD (USA) (2004-2005)



COOLING SYSTEM Capacity: 9,4 liter, Capacity: 9,6 liter (+ Transmission oil cooler)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Coolant SP 14+			
Check every 15000 miles/ 18 months, change every 50000 miles/ 60 months			
USE		CLIMATE	
First change only		Moderate	
PRODUCT RECOMMENDATION 1			
Coolant SP 14+			
01 1 15000 11 1 10 11 1	100000 11 (100 11		

Check every 15000 miles/ 18 months, change every 100000 miles/ 120 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.