

LEXUS (EU) GS XL10 GS 300H (2014-2019)**ENGINE 2AR-FSE**

Capacity: 5,9 liter (Dry fill), Capacity: 4,5 liter (Service fill), Filter capacity: 0,4 liter

USE	CLIMATE
Preferred	Moderate

PRODUCT RECOMMENDATION 1

Presteza MSP 0W-20*Change every 15000 km/ 12 months*

USE	CLIMATE
Severe, preferred	Moderate

PRODUCT RECOMMENDATION 1

Presteza MSP 0W-20*Change every 7500 km/ 6 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Duranza ECO 5W-20

PRODUCT RECOMMENDATION 2

Presteza MSP 5W-30

PRODUCT RECOMMENDATION 3

Xedoz FE 5W-30*Change every 15000 km/ 12 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Duranza ECO 5W-20

PRODUCT RECOMMENDATION 2

Presteza MSP 5W-30

PRODUCT RECOMMENDATION 3

Xedoz FE 5W-30*Change every 7500 km/ 6 months***DIFFERENTIAL REAR**

Capacity: 1,3-1,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1071*Change every 30000 km/ 48 months*

LEXUS (EU) GS XL10 GS 300H (2014-2019)**TRANSAXLE AUTOMATIC L210 2/1**

Capacity: 3,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036*Check every 48 months/ 60000 km*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036*Check every 45000 km/ 36 months, change every 90000 km/ 72 months***HYDRAULIC BRAKE SYSTEM**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3*Change every 24 months***COOLING SYSTEM**

Capacity: 8,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 14+*Check every 30000 km, change every 90000 km*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 14+*Check every 30000 km, change every 150000 km*

LEXUS (EU) GS XL10 GS 300H (2014-2019)**COOLING SYSTEM INVERTER**

Capacity: 2,1 liter (L.H.D.), Capacity: 2,3 liter (R.H.D.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

Check every 30000 km, change every 90000 km

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

*Check every 30000 km, change every 150000 km***AIRCONDITIONING R-1234yf**

Capacity: 470-530 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING R-134a

Capacity: 520-620 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING COMPRESSOR

Capacity: 120-135 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.