LEXUS (EU) LX J200 LX 570 URJ200 (2010-2012)



ENGINE 3UR-FE Capacity: 8,4 liter (Dry fill blue dipstick), Ca Capacity: 7,5 liter (Service fill green dipstic		acity: 7 liter (Service fill blue dipstick),
use Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 Presteza MSP 0W-20	PRODUCT RECOMMENDATION 2 Duranza ECO 5W-20	PRODUCT RECOMMENDATION 3 Presteza MSP 5W-30

DIFFERENTIAL FRONT Capacity: 1,85-1,95 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 1071	
	1

DIFFERENTIAL REAR Capacity: 4,15-4,25 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 1071	

TRANSFERBOX JF2A Capacity: 1,4-1,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 1081	

TRANSMISSION AUTOMATIC AB60F Capacity: 10,4 liter (Dry fill), Capacity: 3	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4036	

LEXUS (EU) LX J200 LX 570 URJ200 (2010-2012)



HYDRAULIC BRAKE SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	

SP Matic 2032	ATF Almirol	ATF Dexron II-D
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Normal		Moderate
USE		CLIMATE
POWER STEERING		

COOLING SYSTEM Capacity: 16,2 liter, Capacity: 16,7 li	ter (+ Transmission oil cooler)		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Coolant SP 14+			

AIRCONDITIONING R-134a Capacity: 920-1010 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING COMPRESSOR R-134a Capacity: 135-155 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.