

# LEXUS (EU) LX J200 LX 570 URJ200 (2012-2015)

**ENGINE 3UR-FE**

Capacity: 9,3 liter (Dry fill), Capacity: 7,5 liter (Service fill), Filter capacity: 0,4 liter

**USE**

Normal

**CLIMATE**

Mediterranean

## PRODUCT RECOMMENDATION 1

**Bi-Turbo 20W-50****USE**

Normal

**CLIMATE**

Moderate

## PRODUCT RECOMMENDATION 1

**Presteza MSP 0W-20**

## PRODUCT RECOMMENDATION 2

**Duranza ECO 5W-20**

## PRODUCT RECOMMENDATION 3

**Presteza MSP 5W-30****DIFFERENTIAL FRONT**

Capacity: 1,85-1,95 liter

**USE**

Normal

**CLIMATE**

Moderate

## PRODUCT RECOMMENDATION 1

**SP Gear 1071****DIFFERENTIAL REAR**

Capacity: 4,15-4,25 liter

**USE**

Normal

**CLIMATE**

Moderate

## PRODUCT RECOMMENDATION 1

**SP Gear 1071****TRANSFERBOX JF2A**

Capacity: 1,4-1,5 liter

**USE**

Normal

**CLIMATE**

Moderate

## PRODUCT RECOMMENDATION 1

**SP Gear 1081**

# LEXUS (EU) LX J200 LX 570 URJ200 (2012-2015)



**TRANSMISSION AUTOMATIC** AB60F 6/1  
Capacity: 10,4 liter (Dry fill), Capacity: 3 liter (Service fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>SP Matic 4036</b>		

## HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Drauliquid DOT 3</b>		

## POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>SP Matic 2032</b>	<b>ATF Almirol</b>	<b>ATF Dexron II-D</b>

## COOLING SYSTEM

Capacity: 16,2 liter, Capacity: 16,7 liter (+ Transmission oil cooler)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant SP 14+</b>		

## AIRCONDITIONING R-134a

Capacity: 870-1020 grams, Capacity: 920-1060 grams (+ coolbox)

We are unable to give a standard recommendation for this component. Please contact our service department.

## AIRCONDITIONING COMPRESSOR R-134a

Capacity: 135-155 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*