LEXUS (EU) NX XZ10 NX 300H AWD AYZ (2014-2019)



ENGINE 2AR-FXE		
	,4 liter (Service fill), Filter capacity: 0,4 lit	er
USE		CLIMATE
Severe (preferred)		Moderate
PRODUCT RECOMMENDATION 1		
Presteza MSP 0W-20		
Change every 7500 km/ 6 months		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Duranza ECO 5W-20	Presteza MSP 5W-30	Xedoz FE 5W-30
Change every 15000 km/ 12 months		
USE		CLIMATE
Normal (preferred)		Moderate
PRODUCT RECOMMENDATION 1		
Presteza MSP 0W-20		
Change every 15000 km/ 12 months		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Duranza ECO 5W-20	Presteza MSP 5W-30	Xedoz FE 5W-30
Change every 7500 km/ 6 months		
DIFFERENTIAL REAR Q211		
Capacity: 1,8 liter		OLIMATE
use Normal		climate Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4036		
Check every 45000 km/ 36 months		
USE		CLIMATE
DOL		CLIWIATE

Severe

PRODUCT RECOMMENDATION 1

SP Matic 4036

Check every 45000 km/36 months, change every 90000 km/72 months

Moderate

LEXUS (EU) NX XZ10 NX 300H AWD AYZ (2014-2019)



TRANSAXLE CVT P314 1/1 Capacity: 3,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4036		
Check every 48 months/ 60000 km		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4036		
Check every 45000 km/ 36 months, change	e every 90000 km/ 72 months	
HYDRAULIC BRAKE SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
Change every 30000 km/ 24 months		

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		
Check every 30000 km, change every 90	000 km	
USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

LEXUS (EU) NX XZ10 NX 300H AWD AYZ (2014-2019)



COOLING SYSTEM INVERTER Capacity: 3,1 liter USE CLIMATE Normal Moderate PRODUCT RECOMMENDATION 1 Coolant SP 14+ Check every 30000 km, change every 90000 km USE CLIMATE First change only Moderate PRODUCT RECOMMENDATION 1 Coolant SP 14+ Check every 30000 km, change every 240000 km

AIRCONDITIONING R-1234yf Capacity: 450-550 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING R-134a

Capacity: 450-550 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING COMPRESSOR

Capacity: 105-135 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.