

LEXUS (EU) RX L1 RX 350 AWD (2012-2015)**ENGINE 2GR-FE**

Capacity: 7,1 liter (Dry fill), Capacity: 6,1 liter (Service fill), Filter capacity: 0,4 liter

USE

Preferred

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Presteza MSP 0W-20***Change every 15000 km/ 12 months***USE**

Severe, preferred

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Presteza MSP 0W-20***Change every 7500 km/ 6 months***USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Duranza ECO 5W-20****PRODUCT RECOMMENDATION 2****Presteza MSP 5W-30****PRODUCT RECOMMENDATION 3****Xedoz FE 5W-30***Change every 15000 km/ 12 months***USE**

Severe

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Duranza ECO 5W-20****PRODUCT RECOMMENDATION 2****Presteza MSP 5W-30****PRODUCT RECOMMENDATION 3****Xedoz FE 5W-30***Change every 7500 km/ 6 months***DIFFERENTIAL REAR**

Capacity: 0,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Gear 1071***Change every 30000 km/ 48 months*

LEXUS (EU) RX L1 RX 350 AWD (2012-2015)

TRANSAXLE AUTOMATIC U660F 6/1
Capacity: 6,7 liter (Dry fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 4036		

Check every 45000 km/ 36 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 4036		

Check every 45000 km/ 36 months, change every 90000 km/ 72 months

TRANSFERBOX AUTOMATIC 10365
Capacity: 0,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Gear 1071		

Change every 30000 km/ 48 months

HYDRAULIC BRAKE SYSTEM ABS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Change every 30000 km/ 24 months

POWER STEERING

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

Check every 24 months/ 30000 km

LEXUS (EU) RX L1 RX 350 AWD (2012-2015)**COOLING SYSTEM**

Capacity: 9,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 14+*Check every 30000 km, change every 90000 km*

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 14+*Check every 30000 km, change every 150000 km*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.