LEXUS (EU) RX XU30 RX 400H AWD (2005-2006)



ENGINE 3MZ-FE Capacity: 5,5 liter (Dry fill), Capacity: 4,7 li	ter (Service fill), Filter capacity: 0,2 liter	
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Bi-Turbo 20W-50		
Change every 15000 km/ 12 months		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 5W-30	Asyntho 5W-30	Bi-Turbo 15W-40
Change every 15000 km/ 12 months		
USE		CLIMATE
Severe		Mediterranean
PRODUCT RECOMMENDATION 1		
Bi-Turbo 20W-50		
Change every 7500 km/ 6 months		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 5W-30	Asyntho 5W-30	Bi-Turbo 15W-40
Change every 7500 km/ 6 months		
DIFFERENTIAL REAR ELECTRIC DRIVE Capacity: 1,8 liter	Q211	

SP Matic 4036	
PRODUCT RECOMMENDATION 1	
Normal	Moderate
USE	CLIMATE

Check every 45000 km/ 36 months

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4036		
Check every 45000 km/ 36 months, change every 90000 km/ 72 months		

LEXUS (EU) RX XU30 RX 400H AWD (2005-2006)



TRANSAXLE HYBRID SYSTEM P310 1/1 Capacity: 4,2 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
SP Matic 4036				
Check every 45000 km/ 36 months				
USE		CLIMATE		
Severe		Moderate		
PRODUCT RECOMMENDATION 1				
SP Matic 4036				
Check every 45000 km/ 36 months, chang	e every 90000 km/ 72 months			

 HYDRAULIC BRAKE SYSTEM ABS

 use
 CLIMATE

 Normal
 Moderate

 PRODUCT RECOMMENDATION 1
 CLIMATE

Drauliquid DOT 3

Change every 30000 km/ 24 months

COOLING SYSTEM Capacity: 10,3 liter, Capacity: 3,4 liter (Electric motor)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Coolant SP 14+				
Check every 30000 km, change every 90000 km				
USE		CLIMATE		
First change only		Moderate		
PRODUCT RECOMMENDATION 1				
Coolant SP 14+				
Check every 30000 km, change every 150000 km				

Check every 30000 km, change every 150000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.