

LINCOLN MKT MKT 3.5 V6 ECOBOOST

(2012-2012)



ENGINE EcoBoost
Capacity: 5,2 liter

USE	CLIMATE
Flexible (max)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Duranza LSP 5W-30	Xedoz FE 5W-30

Change every 10000 miles/ 12 months

TRANSAXLE AUTOMATIC 6F50 6/1
Capacity: 10,3 liter (Dry fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
SP Matic 4036	

Change every 150000 miles

TRANSAXLE AUTOMATIC 6F55 6/1
Capacity: 11 liter (Dry fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
SP Matic 4036	

Change every 150000 miles

HYDRAULIC BRAKE SYSTEM
Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	

LINCOLN MKT MKT 3.5 V6 ECOBOOST

(2012-2012)

**COOLING SYSTEM**

Capacity: 13 liter

USE		CLIMATE
Normal, green fluid		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Change every 50000 miles/ 36 months

USE		CLIMATE
First change only, green fluid		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Change every 100000 miles/ 72 months

USE		CLIMATE
First change only, orange fluid		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Change every 100000 miles/ 72 months

USE		CLIMATE
Normal, orange fluid		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Change every 50000 miles/ 36 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.