LINCOLN MKX MKX 3.7 V6 TI-VCT AWD (2011-2011)



| ENGINE Duratec 37 Capacity: 5,2 liter | |
|--|----------|
| USE | CLIMATE |
| Severe | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Duranza ECO 5W-20 | |
| Change every 5000 miles/ 6 months | |
| USE | CLIMATE |
| Flexible (max) | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Duranza ECO 5W-20 | |
| O I (0000 II (100 II | |

Change every 10000 miles/ 12 months

| DIFFERENTIAL REAR Capacity: 1,15 liter | |
|---|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Gearlube GL-5 80W-90 | |
| Ohanna anna 150000 millea | |

Change every 150000 miles

| TRANSAXLE AUTOMATIC 6F50 6/1 Capacity: 10,5 liter (Dry fill) | |
|---|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| SP Matic 4036 | |

Change every 150000 miles

| USE | CLIMATE |
|--------------------------|----------|
| Severe | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| SP Matic 4036 | |
| | |

Change every 30000 miles

LINCOLN MKX MKX 3.7 V6 TI-VCT AWD (2011-2011)



| TRANSFERBOX Capacity: 0,35 liter | |
|-------------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Gearlube Racing 75W-140 | |

| HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.) | |
|--|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Drauliquid DOT 3 | |

| POWER STEERING Capacity: 0-0 liter (Between min and max.) | |
|---|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| SP Matic 2032 | |

| COOLING SYSTEM Capacity: 11,1 liter, Capacity: 11,3 | liter (With Trailer Tow Package) | |
|--|----------------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Coolant SP 15+ | Coolant SP 12 | Coolant -38 Organic NF |
| Check every 6 months, change eve | ery 50000 miles/ 36 months | I |

| USE | | CLIMATE |
|--------------------------|--------------------------|--------------------------|
| First change only | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Coolant SP 15+ | Coolant SP 12 | Coolant -38 Organic NF |

Check every 6 months, change every 100000 miles/72 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.