

# LINCOLN NAVIGATOR (L) NAVIGATOR (L)

## 5.4 V8 24V (2012-2012)

**ENGINE**

Capacity: 6,6 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Duranza ECO 5W-20***Change every 7500 miles/ 6 months***DIFFERENTIAL REAR**

Capacity: 2,1 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Gearlube Racing 75W-140***Change every 150000 miles***TRANSMISSION AUTOMATIC 6R80 6/1**

Capacity: 12,4 liter (Dry fill)

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****SP Matic 4036***Change every 150000 miles***HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Drauliquid DOT 3***Change every 24 months***POWER STEERING**

Capacity: 0-0 liter (Between min and max.)

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****SP Matic 2032**

# LINCOLN NAVIGATOR (L) NAVIGATOR (L)

## 5.4 V8 24V (2012-2012)



### COOLING SYSTEM

Capacity: 15,5 liter, Capacity: 18 liter (+ rear heater), Capacity: 16 liter (Heavy Duty), Capacity: 18,5 liter (Heavy duty + rear heater)

| USE                      |                          | CLIMATE                       |
|--------------------------|--------------------------|-------------------------------|
| Normal                   |                          | Moderate                      |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3      |
| <b>Coolant SP 15+</b>    | <b>Coolant SP 12</b>     | <b>Coolant -38 Organic NF</b> |

*Change every 45000 miles/ 36 months*

| USE                      |                          | CLIMATE                       |
|--------------------------|--------------------------|-------------------------------|
| First change only        |                          | Moderate                      |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3      |
| <b>Coolant SP 15+</b>    | <b>Coolant SP 12</b>     | <b>Coolant -38 Organic NF</b> |

*Change every 105000 miles/ 72 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*