

LOTUS EXIGE MK3 EXIGE S (2012-2016)**ENGINE 2GR-FE**

Capacity: 6,8 liter (Dry fill), Capacity: 7,1 liter (Dry fill, with heat exchanger), Capacity: 4 liter (Oil cooler), Capacity: 6,1 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar MSP+ 5W-40	Specialsynth MSP 5W-40	Emperol 5W-40

Change every 15000 km/ 12 months

USE	CLIMATE
Track day/racing	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar 0W-40		

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar MSP+ 5W-40	Specialsynth MSP 5W-40	Emperol 5W-40

Change every 7500 km/ 6 months

TRANSAXLE AUTOMATIC IPS 6/1

Capacity: 6,4 liter (Dry fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 4036		

Change every 58000 km/ 48 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 4036		

Change every 7500 km/ 6 months

TRANSAXLE MANUAL 6/1

Capacity: 2,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 5015		

Check every 45000 km, change every 90000 km/ 72 months

LOTUS EXIGE MK3 EXIGE S (2012-2016)**HYDRAULIC BRAKE/CLUTCH SYSTEM**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
<i>Check every 15000 km/ 12 months, change every 30000 km/ 24 months</i>		

COOLING SYSTEM

Capacity: 12,9 liter (with automatic transmission), Capacity: 17 liter (with manual transmission)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	
<i>Check every 15000 km/ 12 months, change every 48 months</i>		

AIRCONDITIONING SYSTEM

Capacity: 450 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.