## MASERATI 3200 GT 3200 GT (1998-2001)



<b>ENGINE</b> Capacity: 7 liter, Filter capacity: 0,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Emperol Racing 10W-60	
	'

Change every 20000 km/ 12 months

USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	

Check every 20000 km, change every 40000 km/24 months

TRANSMISSION AUTOMATIC BT Capacity: 4 liter	₹ 4/1		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Matic 2032	ATF Almirol		

Check every 20000 km, change every 40000 km/24 months

TRANSMISSION MANUAL Getrag Capacity: 1,7 liter	g 6/1	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube GL-4 80W	
Change every 20000 km/ 12 month	'S	

HYDRAULIC BRAKE/CLUTCH SYSTEM ABS Capacity: 1,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4 Drauliquid-S DOT 4		
Check every 20000 km, change every 24 months		

## MASERATI 3200 GT 3200 GT (1998-2001)



POWER STEERING Capacity: 1,7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
Charles arong 20000 km change arong 24 months		

Check every 20000 km, change every 24 months

COOLING SYSTEM Capacity: 14 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	
Chock overy 20000 km, change overy 24 months	·

Check every 20000 km, change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.