MASERATI QUATTROPORTE QUATTROPORTE V6 (1995-2001)



ENGINE AM 574 Capacity: 6,5 liter, Capacity: 7,5 liter (Dry fill), Filter capacity: 0,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Emperol Racing 10W-60		
Change every 15000 km		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
Emperol Racing 10W-60		
Change every 5000 km		

DIFFERENTIAL REAR LIMITED SLIP Capacity: 1,7 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Check every 10000 km, change every 40000 km	

TRANSMISSION AUTOMATIC ZF 4/1 Capacity: 4 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 2032	

TRANSMISSION MANUAL Getrag Capacity: 1,7 liter	g 6/1	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube GL-4 80W	
Check every 10000 km, change every 40000 km		

KROON-OIL B.V. Postbus 149 7600 AC Almelo

Check every 10000 km, change every 30000 km

MASERATI QUATTROPORTE QUATTROPORTE V6 (1995-2001)



HYDRAULIC BRAKE/CLUTCH SYSTEM A Capacity: 0,5 liter	ABS	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Check every 10000 km, change every 60000 km/24 months

POWER STEERING Capacity: 1,7 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	
Check every 10000 km	

COOLING SYSTEM Capacity: 14 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	
Chock overy 10000 km, change every 24 months	'

Check every 10000 km, change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.