MAZDA (EU) 2 DJ/DL 2 SKYACTIV-G 1.5 (85 KW) (2015 AND AFTER)



ENGINE SKYACTIV-G 1.5 Capacity: 4,7 liter (Dry fill), Capacity: 4,2 liter (Service fill), Filter capacity: 0,3 liter				
USE		CLIMATE		
Severe		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Presteza MSP 0W-20	Helar SP LL-03 5W-30	Presteza MSP 5W-30		
Change every 10000 km/ 6 months				
USE		CLIMATE		
Flexible (max)		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Presteza MSP 0W-20	Helar SP LL-03 5W-30	Presteza MSP 5W-30		
Change every 20000 km/ 12 months				

TRANSAXLE MANUAL F66M-R 6/1 Capacity: 1,6 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 5015	
Change every 180000 km	

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3
Change every 40000 km/ 24 months		
JSE		CLIMATE
Severe		Moderate
RODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
	Drauliquid-S DOT 4	Drauliquid DOT 3

MAZDA (EU) 2 DJ/DL 2 SKYACTIV-G 1.5 (85 KW) (2015 AND AFTER)



COOLING SYSTEM Capacity: 5-5,6 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Coolant SP 14+				
Check every 40000 km/ 24 months, change every 100000 km/ 60 months				
USE		CLIMATE		
First change only		Moderate		
PRODUCT RECOMMENDATION 1				
Coolant SP 14+				
Check every 40000 km/ 24 months, change every 200000 km/ 120 months				

AIRCONDITIONING COMPRESSOR R-1234yf

Capacity: 110 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING COMPRESSOR R-134a

Capacity: 110 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM R-1234yf

Capacity: 335-385 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM R-134a

Capacity: 395-445 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.