

# MAZDA (EU) 2 DE 2 1.6 CITD (70 KW) DPF (2010-2015)

**ENGINE** MZ-CD 1.6

Capacity: 4,9 liter (Dry fill), Capacity: 3,9 liter (Service fill), Filter capacity: 0,4 liter

USE		CLIMATE
Normal		Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Duranza LSP 5W-30</b>	<b>Asyntho 5W-30</b>	<b>Emperol 10W-40</b>

*Change every 20000 km/ 12 months*

USE		CLIMATE
Severe		Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Duranza LSP 5W-30</b>	<b>Asyntho 5W-30</b>	<b>Emperol 10W-40</b>

*Change every 10000 km***TRANSAXLE AUTOMATIC** FN4A-EL 4/1

Capacity: 5 liter (Dry fill), Capacity: 3 liter (Service fill)

USE		CLIMATE
Normal		Moderate

PRODUCT RECOMMENDATION 1		
<b>SP Matic 4026</b>		

*Check every 20000 km/ 12 months***TRANSAXLE MANUAL** B65M-R 5/1

Capacity: 2,3 liter

USE		CLIMATE
Normal		Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>SP Gear 1011</b>	<b>Syngear TDL 75W-90</b>	

*Check every 20000 km/ 12 months*

# MAZDA (EU) 2 DE 2 1.6 CITD (70 KW) DPF (2010-2015)



## HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	<b>Drauliquid DOT 3</b>

*Change every 40000 km/ 24 months*

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	<b>Drauliquid DOT 3</b>

*Change every 20000 km/ 12 months*

## HYDRAULIC CLUTCH SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	<b>Drauliquid DOT 3</b>

*Check every 20000 km, change every 40000 km/ 24 months*

## COOLING SYSTEM

Capacity: 6,5 liter

USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
<b>Coolant SP 14+</b>		

*Change every 200000 km*

## AIRCONDITIONING COMPRESSOR

Capacity: 120 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

## AIRCONDITIONING SYSTEM

Capacity: 500-550 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*