

MAZDA (EU) 6 GG/GY 6 2.0 (2002-2005)**ENGINE LF**

Capacity: 4,6 liter (Dry fill), Capacity: 4,3 liter (Service fill), Filter capacity: 0,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Duranza LSP 5W-30	Asyntho 5W-30	Emperol 10W-40

Change every 20000 km/ 12 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Duranza LSP 5W-30	Asyntho 5W-30	Emperol 10W-40

*Change every 10000 km/ 12 months***TRANSAXLE AUTOMATIC FN4A-EL 4/1**

Capacity: 7,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 4026		

*Check every 60000 km/ 36 months***TRANSAXLE MANUAL G35M-R 5/1**

Capacity: 2,87 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Gearlube GL-5 80W-90	

Change every 100000 km/ 60 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Syngear 75W-90

Change every 100000 km/ 60 months

**HYDRAULIC BRAKE/CLUTCH SYSTEM ABS**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Check every 20000 km, change every 40000 km/ 24 months

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Check every 20000 km, change every 12 months

POWER STEERING

Capacity: 0,8-0,9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2032		

Check every 20000 km/ 12 months

COOLING SYSTEM

Capacity: 7,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		

Check every 20000 km, change every 24 months

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		

Check every 30000 km/ 24 months, change every 90000 km/ 48 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.