

**MAZDA (EU) 6 GG/GY 6 2.3 S-VT (2002-2007)****ENGINE L3**

Capacity: 4,4 liter, Capacity: 3,5 liter (+ twisted dipstick), Filter capacity: 0,4 liter

| USE                      |                          | CLIMATE                  |
|--------------------------|--------------------------|--------------------------|
| Normal                   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>Duranza LSP 5W-30</b> | <b>Asyntho 5W-30</b>     | <b>Emperol 10W-40</b>    |

*Change every 20000 km/ 12 months*

| USE                      |                          | CLIMATE                  |
|--------------------------|--------------------------|--------------------------|
| Severe                   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>Duranza LSP 5W-30</b> | <b>Asyntho 5W-30</b>     | <b>Emperol 10W-40</b>    |

*Change every 10000 km/ 12 months***TRANSAXLE AUTOMATIC FS5A-EL 5/1**

Capacity: 8,15 liter (Dry fill), Capacity: 3 liter (Service fill)

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>SP Matic 4026</b>     |  |          |

*Check every 40000 km/ 24 months***TRANSAXLE MANUAL G35M-R 5/1**

Capacity: 2,87 liter

| USE                         |                             | CLIMATE       |
|-----------------------------|-----------------------------|---------------|
| Normal                      |                             | Mediterranean |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2    |               |
| <b>Gearlube GL-4 80W-90</b> | <b>Gearlube GL-5 80W-90</b> |               |

*Change every 100000 km/ 60 months*

| USE                      |                           | CLIMATE                  |
|--------------------------|---------------------------|--------------------------|
| Normal                   |                           | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3 |
| <b>SP Gear 1011</b>      | <b>Syngear TDL 75W-90</b> | <b>Syngear 75W-90</b>    |

*Change every 100000 km/ 60 months*

**MAZDA (EU) 6 GG/GY 6 2.3 S-VT (2002-2007)****TRANSAXLE MANUAL G36M-R 6/1**

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2    |  |
|-----------------------------|-----------------------------|--|
| <b>Gearlube GL-4 80W-90</b> | <b>Gearlube GL-5 80W-90</b> |  |

| USE    | CLIMATE |
|--------|---------|
| Normal | Arctic  |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2   | PRODUCT RECOMMENDATION 3 |
|--------------------------|----------------------------|--------------------------|
| <b>SP Gear 5015</b>      | <b>Gearlube RPC 75W-80</b> | <b>SP Gear 1071</b>      |

**HYDRAULIC BRAKE/CLUTCH SYSTEM ABS**

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3 |
|----------------------------------|---------------------------|--------------------------|
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> | <b>Drauliquid DOT 3</b>  |

*Check every 20000 km, change every 40000 km/ 24 months*

| USE    | CLIMATE  |
|--------|----------|
| Severe | Moderate |

| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3 |
|----------------------------------|---------------------------|--------------------------|
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> | <b>Drauliquid DOT 3</b>  |

*Check every 20000 km, change every 12 months*

**POWER STEERING**

Capacity: 0,8 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 |  |  |
|--------------------------|--|--|
| <b>SP Matic 2032</b>     |  |  |

*Check every 20000 km/ 12 months*

**MAZDA (EU) 6 GG/GY 6 2.3 S-VT (2002-2007)****COOLING SYSTEM**

Capacity: 7,5 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**Coolant -38 Organic NF***Check every 20000 km, change every 24 months*

| USE               | CLIMATE  |
|-------------------|----------|
| First change only | Moderate |

## PRODUCT RECOMMENDATION 1

**Coolant -38 Organic NF***Check every 30000 km/ 24 months, change every 90000 km/ 48 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*