MAZDA (EU) 626 626 2.0 DIESEL (1987-1992)



ENGINE RF Capacity: 5 liter, Filter capacity: 0,5 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Bi-Turbo 15W-40		
Change every 10000 km/ 6 months		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Emperol 10W-40		
Change every 10000 km/ 6 months		

TRANSAXLE AUTOMATIC 3/1 Capacity: 6,3 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Matic 2032	ATF Dexron II-D		

TRANSAXLE MANUAL 5/1 Capacity: 3,4 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-4 80W-90	Gearlube GL-5 80W-90	ATF Dexron II-D
Check every 1000 km/ 6 months, ch	nange every 80000 km/ 48 months	'

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

MAZDA (EU) 626 626 2.0 DIESEL (1987-1992)



POWER STEERING		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Dexron II-D	

GREASE POINTS/NIPPLES WHEEL BEARINGS REAR		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Change even 45000 km/ 26 month	20	

Change every 45000 km/36 months

COOLING SYSTEM Capacity: 9 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	
Change every 24 months	,

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.