

# MAZDA (EU) MPV LW MPV 3.0 V6-24V (2003-2005)

**ENGINE AJ**

Capacity: 5,7 liter, Filter capacity: 0,5 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|--------------------------|--------------------------|--------------------------|
| <b>Duranza ECO 5W-20</b> | <b>Duranza LSP 5W-30</b> | <b>Asyntho 5W-30</b>     |

*Change every 20000 km/ 12 months*

| USE    | CLIMATE  |
|--------|----------|
| Severe | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|--------------------------|--------------------------|--------------------------|
| <b>Duranza ECO 5W-20</b> | <b>Duranza LSP 5W-30</b> | <b>Asyntho 5W-30</b>     |

*Change every 10000 km***TRANSAXLE AUTOMATIC 5/1**

Capacity: 9,7 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 |  |  |
|--------------------------|--|--|
| <b>SP Matic 2032</b>     |  |  |

*Check every 24 months/ 30000 km***HYDRAULIC BRAKE SYSTEM**

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3 |
|----------------------------------|---------------------------|--------------------------|
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> | <b>Drauliquid DOT 3</b>  |

*Check every 20000 km, change every 40000 km/ 24 months***HYDRAULIC CLUTCH SYSTEM**

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3 |
|----------------------------------|---------------------------|--------------------------|
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> | <b>Drauliquid DOT 3</b>  |

*Check every 20000 km/ 12 months*

**MAZDA (EU) MPV LW MPV 3.0 V6-24V (2003-2005)****POWER STEERING**

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>SP Matic 2032</b>     | <b>ATF Dexron II-D</b>   |          |

*Check every 20000 km/ 12 months*

**COOLING SYSTEM**

Capacity: 10,6 liter, Capacity: 12,4 liter (+ rear heater)

| USE                           |  | CLIMATE  |
|-------------------------------|--|----------|
| Normal                        |  | Moderate |
| PRODUCT RECOMMENDATION 1      |  |          |
| <b>Coolant -38 Organic NF</b> |  |          |

*Check every 40000 km/ 24 months, change every 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*