MAZDA (EU) MX-3 MX-3 1.6I (1992-1998)



USE CLIMA	
	ATE
Normal Mode	lerate
PRODUCT RECOMMENDATION 1	
Asyntho 5W-30	

Check every 3000 km, change every 10000 km/12 months

TRANSAXLE AUTOMATIC 4/1 Capacity: 6,3 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Matic 2032	ATF Dexron II-D		

TRANSAXLE MANUAL 5/1 Capacity: 2,7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Syngear 75W-90
Check every 40000 km/24 months, chang	ge every 80000 km/ 48 months	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
Check every 40000 km/24 months, change	ge every 80000 km/ 48 months	

HYDRAULIC BRAKE/CLUTCH SYSTEM USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	Moderate
Drauliquid DOT 3	
Check every 10000 km, change every 40000 km/ 24 months	

MAZDA (EU) MX-3 MX-3 1.6I (1992-1998)



POWER STEERING Capacity: 0,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Dexron II-D	
Check every 10000 km		

COOLING SYSTEM Capacity: 6 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	
Change every 24 months	·

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.