

# MERCEDES-BENZ (EU) CLS-CLASS C218 / X218 CLS 250 D 4MATIC 218.397/997 (2015-2018)



**ENGINE** OM651.924  
Capacity: 6,5 liter

## USE

Flexible (max)

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Helar SP LL-03 0W-30**

## PRODUCT RECOMMENDATION 2

**Helar SP LL-03 5W-30**

## PRODUCT RECOMMENDATION 3

**Presteza MSP 5W-30***Change every 25000 km***DIFFERENTIAL FRONT**

Capacity: 0,6 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**SP Gear 1071****DIFFERENTIAL REAR**

Capacity: 1,1-1,2 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**SP Gear 1071****TRANSFERBOX**

Capacity: 0,65 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**SP Matic 2094***Change every 125000 km/ 60 months***TRANSMISSION AUTOMATIC 722.96x 7/1**

Capacity: 9,7 liter (Dry fill)

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**SP Matic 2094***Change every 125000 km/ 60 months*

# MERCEDES-BENZ (EU) CLS-CLASS C218 / X218 CLS 250 D 4MATIC 218.397/997 (2015-2018)



## HYDRAULIC BRAKE SYSTEM ABS

Capacity: 1,1 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Drauliquid-S DOT 4***Change every 24 months*

## COOLING SYSTEM

Capacity: 10,4 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Coolant SP 12 EVO***Change every 250000 km/ 180 months*

## AIRCONDITIONING COMPRESSOR

Capacity: 120 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

## AIRCONDITIONING SYSTEM

Capacity: 590 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*