MERCEDES-BENZ (EU) B-CLASS W245 B 200 245.233 (2005-2007)



Capacity: 5 liter USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30	Presteza MSP 5W-30

This vehicle is equipped with ASSYST or ASSYST Plus. ASSYST indicates when the vehicle needs Service.

TRANSAXLE AUTOMATIC 722.8x (CVT) 1/1 Capacity: 4 liter, Capacity: 6 liter (+ torque converter)				
USE	CLIMATE			
Normal	Moderate			
PRODUCT RECOMMENDATION 1				
SP Matic 4016				

This vehicle is equipped with ASSYST or ASSYST Plus. ASSYST indicates when the vehicle needs Service. Change every 60000 km

TRANSAXLE MANUAL 716.5xx 5/1 Capacity: 1,8 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 5015	

This vehicle is equipped with ASSYST or ASSYST Plus. ASSYST indicates when the vehicle needs Service.

HYDRAULIC BRAKE/CLUTCH SYSTEM Capacity: 0,6 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Drauliquid-S DOT 4			
	(07.0)		

This vehicle is equipped with ASSYST or ASSYST Plus. ASSYST indicates when the vehicle needs Service.

MERCEDES-BENZ (EU) B-CLASS W245 B 200 245.233 (2005-2007)



COOLING SYSTEM Capacity: 5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 11	Coolant SP 12 EVO	
This vehicle is equipped with ASSY	/ST or ASSYST Plus. ASSYST indicates wh	en the vehicle needs Service.

This vehicle is equipped with ASSYST or ASSYST Plus. ASSYST indicates when the vehicle needs Service. Change every 250000 km/ 180 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.