## MERCEDES-BENZ (EU) B-CLASS W246 / W242 B 180 246.242 (2011-2014)



ENGINE M270.910 Capacity: 5,8 liter		
USE		CLIMATE
Extended drain (max)		Moderate
PRODUCT RECOMMENDATION 1		
Helar 0W-40		
Change every 25000 km		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30	Presteza MSP 5W-30

Change every 15000 km

TRANSAXLE MANUAL 711.643 6/1 Capacity: 1,8 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 5015	

TRANSAXLE SEMI-AUTOMATIC 724.002 7/1 Capacity: 5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2072		

TRANSAXLE SEMI-AUTOMATIC 724.003 7/1 Capacity: 5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2072		
Change every 100000 km/ 60 months		

## MERCEDES-BENZ (EU) B-CLASS W246 / W242 B 180 246.242 (2011-2014)



HYDRAULIC BRAKE/CLUTCH SYSTEM Capacity: 0,5 liter	
use Normal	сымате Moderate
PRODUCT RECOMMENDATION 1 Drauliquid-S DOT 4	

Change every 24 months

COOLING SYSTEM Capacity: 7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 11	Coolant SP 12 EVO	

Change every 200000 km/ 120 months

## AIRCONDITIONING COMPRESSOR Capacity: 120 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

## AIRCONDITIONING SYSTEM

Capacity: 550-650 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.