

ENGINE M111 Capacity: 5,5 liter	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Bi-Turbo 20W-50	

Service intervals for vehicles with ASSYST, from 1.6.1997 onwards: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service B: <22000 k Change every 15000 km/12 months

use Normal		climate Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar 0W-40	Emperol 5W-40	Emperol 5W-50

Service intervals for vehicles with ASSYST, from 1.6.1997 onwards: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service B. If the last service was a Service B: <22000 k Change every 15000 km/12 months

DIFFERENTIAL REAR Capacity: 0,7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1071	Gearlube LS 80W-90	

Service intervals for vehicles with ASSYST, from 1.6.1997 onwards: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service B: <22000 k Check every 30000 km

DIFFERENTIAL REAR LIMITED SLIP Capacity: 1,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1071	Gearlube LS 80W-90	

Service intervals for vehicles with ASSYST, from 1.6.1997 onwards: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service B: <22000 k Check every 30000 km



TRANSMISSION AUTOMATIC 722.4xx 4/1 Capacity: 5,5 liter			
USE CLIMATE			
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
SP Matic 4026 SP Matic 2032 ATF Almirol			

Service intervals for vehicles with ASSYST, from 1.6.1997 onwards: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service B: <22000 k Check every 30000 km, change every 60000 km

TRANSMISSION AUTOMATIC 722.6xx 5/1 Capacity: 8 liter		
USE CLIMATE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		

Service intervals for vehicles with ASSYST, from 1.6.1997 onwards: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service B: <22000 k Check every 30000 km

TRANSMISSION MANUAL 717.4XX AS OF PRODUCTION NR. 7 340 241 5/1 Capacity: 1,5 liter		
USE		CLIMATE
		NA · -
Normal		Moderate
Normal PRODUCT RECOMMENDATION 1		Moderate

Service intervals for vehicles with ASSYST, from 1.6.1997 onwards: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service B: <22000 k Check every 30000 km

TRANSMISSION MANUAL 717.4XX UP TO PRODUCTION NR. 7 340 240 5/1 Capacity: 1,5 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
SP Matic 4026 SP Matic 2032 ATF-A			

Service intervals for vehicles with ASSYST, from 1.6.1997 onwards: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service B: <22000 k Check every 30000 km



HYDRAULIC LEVELLING SYSTEM Capacity: 2 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Fluid 3023	

Service intervals for vehicles with ASSYST, from 1.6.1997 onwards: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service B: <22000 k Check every 30000 km

HYDRAULIC BRAKE/CLUTCH SYSTEM		
USE	CLIMATE	
Normal	Moder	ate
PRODUCT RECOMMENDATION 1		
Drauliquid-S DOT 4		

Service intervals for vehicles with ASSYST, from 1.6.1997 onwards: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service B: <22000 k Change every 24 months

POWER STEERING Capacity: 1 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Matic 4026	SP Matic 2032		

Service intervals for vehicles with ASSYST, from 1.6.1997 onwards: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service B: <22000 k Check every 30000 km

GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
HT Q9 High Grade Grease Labora Grease		

Service intervals for vehicles with ASSYST, from 1.6.1997 onwards: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service B: <22000 k Check every 30000 km



COOLING SYSTEM Capacity: 8,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 11		

Service intervals for vehicles with ASSYST, from 1.6.1997 onwards: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service B: <22000 k Change every 36 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.