

PRODUCT RECOMMENDATION

MERCEDES-BENZ (EU) C-CLASS W205 / V205 / S205 / C205 / A205 MERCEDES-AMG C 63 S 205.087/287/387/487 (2015-2021)



ENGINE M177.980
Capacity: 9 liter

USE	CLIMATE
Flexible (max)	Moderate

PRODUCT RECOMMENDATION 1

Helar 0W-40

Change every 20000 km

DIFFERENTIAL REAR
Capacity: 1,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube Racing 75W-140

Change every 50000 km/ 36 months

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Gearlube Racing 75W-140

Change every 3000 km

TRANSMISSION AUTOMATIC 722.9xx 7/1
Capacity: 9 liter (Dry fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2094

Change every 125000 km/ 60 months

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2094

Change every 50000 km/ 36 months

MERCEDES-BENZ (EU) C-CLASS W205 / V205 / S205 / C205 / A205 MERCEDES-AMG C 63 S 205.087/287/387/487 (2015-2021)

**TRANSMISSION AUTOMATIC** 725.0xx 9/1

Capacity: 10-11 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2096*Change every 50000 km/ 36 months***HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-S DOT 4*Change every 24 months***COOLING SYSTEM**

Capacity: 11,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 12 EVO*Change every 200000 km/ 120 months***COOLING SYSTEM INTERCOOLER**

Capacity: 4,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 12 EVO*Change every 200000 km/ 120 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.