MERCEDES-BENZ (EU) CL-CLASS C215 CL 500 215.375 (1999-2006)



ENGINE M113.960 Capacity: 8 liter		
USE	CLIMATE	
Flexible (max)	Mediterrane	an
PRODUCT RECOMMENDATION 1		
Bi-Turbo 20W-50		

Service intervals for vehicles with ASSYST: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service A; >2200

USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar 0W-40	Emperol 5W-40	Emperol 5W-50

Service intervals for vehicles with ASSYST: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service A; >2200

DIFFERENTIAL REAR Capacity: 1,6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1071	Gearlube LS 80W-90	

Service intervals for vehicles with ASSYST: A display indicates when the next service is due. First service for new cars is a Service B. If the last service B. If the last service B: <22000 km ago: Service A, >2200

TRANSMISSION AUTOMATIC 722.6xx 5 Capacity: 9,1 liter	/1	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		

Service intervals for vehicles with ASSYST: A display indicates when the next service is due. First service for new cars is a Service B. If the last service B. If the last service B: <22000 km ago: Service A, >2200

MERCEDES-BENZ (EU) CL-CLASS C215 CL 500 215.375 (1999-2006)



TRANSMISSION AUTOMATIC 722.9xx 7/1 Capacity: 9 liter, Capacity: 6,7 liter (+ code A25)		
USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		

Service intervals for vehicles with ASSYST: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service B: <22000 km ago: Service A, >2200 Change every 60000 km

ACTIVE BODY CONTROL SYSTEM Capacity: 4 liter	
USE	CLIMATE
Normal	 Moderate
PRODUCT RECOMMENDATION 1	
SP Fluid 3013	

Service intervals for vehicles with ASSYST: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service A; >2200

HYDRAULIC BRAKE SYSTEM ABS Capacity: 0,9 liter	
use Normal	climate Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-S DOT 4	

Service intervals for vehicles with ASSYST: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service B: <22000 km ago: Service A, >2200 Change every 24 months

POWER STEERING Capacity: 1,25 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Fluid 3013	

Service intervals for vehicles with ASSYST: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service B: <22000 km ago: Service A, >2200

MERCEDES-BENZ (EU) CL-CLASS C215 CL 500 215.375 (1999-2006)



COOLING SYSTEM Capacity: 11,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 11	Coolant SP 12 EVO	

Service intervals for vehicles with ASSYST: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service B: <22000 km ago: Service A, >2200 Change every 250000 km/ 180 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.