MERCEDES-BENZ (EU) CL-CLASS C216 CL 600 216.376 (2010-2014)



ENGINE M275.953 Capacity: 9 liter	
use Flexible (max)	CLIMATE Moderate
PRODUCT RECOMMENDATION 1 Helar 0W-40	

DIFFERENTIAL REAR 200 FE, Ø Capacity: 1,1 liter	200 mm	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 1071		

DIFFERENTIAL REAR 215 FE, Ø 215 r Capacity: 1,2 liter	nm	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 1071		

Normal CLIMAT Mode	
Normal Mode	:
	rate
PRODUCT RECOMMENDATION 1	
SP Gear 1071	

TRANSMISSION AUTOMATIC 722.6xx 5/1 Capacity: 8 liter (Dry fill), Capacity: 6,5 liter (Service fill)		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		
Change every 60000 km		

MERCEDES-BENZ (EU) CL-CLASS C216 CL 600 216.376 (2010-2014)



ACTIVE BODY CONTROL SYSTEM Capacity: 4 liter (Dry fill)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Fluid 3013	

HYDRAULIC BRAKE SYSTEM ABS Capacity: 0,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-S DOT 4	
Change every 24 months	'

POWER STEERING Capacity: 1 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Fluid 3013	
	<u>'</u>

COOLING SYSTEM Capacity: 0-0 liter (Between min an	d max.)	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 11	Coolant SP 12 EVO	
Change every 36 months	,	

AIRCONDITIONING COMPRESSOR

Capacity: 110 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM

Capacity: 1070 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.