## MERCEDES-BENZ (EU) CLS-CLASS C218 / X218 CLS 350 BLUEEFFICIENCY 218.359 (2010-2012)



ENGINE M276.952 Capacity: 6,5 liter	
USE	CLIMATE
Flexible (max)	Moderate
PRODUCT RECOMMENDATION 1	
Helar 0W-40	

Change every 25000 km

<b>DIFFERENTIAL REAR</b> Capacity: 1,1-1,2 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 1071	

TRANSMISSION AUTOMATIC 722.9XX AS OF PRODUCTION NR. 2834527 722.9xx 7/1 Capacity: 9 liter (Dry fill)			
USE	CLIMATE		
Normal	Moderate		
PRODUCT RECOMMENDATION 1			
SP Matic 2094			
Change every 125000 km/ 60 months	*		

TRANSMISSION AUTOMATIC 722.9XX UP TO PRODUCTION NR. 2834526 722.9xx 7/1 Capacity: 9 liter (Dry fill)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
SP Matic 4026			
Change event 125000 km/ 60 menths			

Change every 125000 km/ 60 months

HYDRAULIC BRAKE SYSTEM ABS Capacity: 1,1 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-S DOT 4	
Change every 24 months	

## MERCEDES-BENZ (EU) CLS-CLASS C218 / X218 CLS 350 BLUEEFFICIENCY 218.359 (2010-2012)



COOLING SYSTEM Capacity: 9,6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 11	Coolant SP 12 EVO	

Change every 250000 km/ 180 months

## AIRCONDITIONING COMPRESSOR Capacity: 120 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM Capacity: 590 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.