

# MERCEDES-BENZ (EU) CLS-CLASS C218 / X218 CLS 500 4MATIC BLUEEFFICIENCY 218.391/991 (2012-2016)

**ENGINE** M278.922

Capacity: 8,5 liter

USE	CLIMATE
Flexible (max)	Moderate

PRODUCT RECOMMENDATION 1

**Helar 0W-40***Change every 25000 km***DIFFERENTIAL FRONT**

Capacity: 0,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**SP Gear 1071****DIFFERENTIAL REAR**

Capacity: 1,1-1,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**SP Gear 1071****TRANSFERBOX**

Capacity: 0,65 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**SP Matic 2094***Change every 125000 km/ 60 months***TRANSMISSION AUTOMATIC** 722.96x 7/1

Capacity: 9,7 liter (Dry fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**SP Matic 2094***Change every 125000 km/ 60 months*

# MERCEDES-BENZ (EU) CLS-CLASS C218 / X218 CLS 500 4MATIC BLUEEFFICIENCY 218.391/991 (2012-2016)


**TRANSMISSION AUTOMATIC 725.041 9/1**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>SP Matic 2096</b>		

*Change every 125000 km/ 60 months*

**HYDRAULIC BRAKE SYSTEM ABS**

Capacity: 1,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Drauliquid-S DOT 4</b>		

*Change every 24 months*

**COOLING SYSTEM**

Capacity: 12,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant SP 12 EVO</b>		

*Change every 250000 km/ 180 months*

**AIRCONDITIONING COMPRESSOR**

Capacity: 120 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

**AIRCONDITIONING SYSTEM**

Capacity: 590 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*