MERCEDES-BENZ (EU) CLS-CLASS C219 CLS 300 219.354 (2009-2010)



01		
Helar 0W-40	Emperol 5W-40	Emperol 5W-50
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Normal		Moderate
USE		CLIMATE
Change every 25000 km/ 12 months		
Helar 0W-40		
PRODUCT RECOMMENDATION 1		
Extended		Moderate
USE		CLIMATE
ENGINE M272.943/944 Capacity: 8 liter		

Change every 15000 km/ 12 months

DIFFERENTIAL REAR Capacity: 1-1,6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1071	Gearlube LS 80W-90	

TRANSMISSION AUTOMATIC 722.9XX AS OF PRODUCTION NR. 2834527 722.9xx 7/1 Capacity: 9 liter (Dry fill)		
USE	CLIMATE	
First change only	Moderate	
PRODUCT RECOMMENDATION 1		
SP Matic 2094		

Change every 60000 km

TRANSMISSION AUTOMATIC 722.9XX UP TO PRODUCTION NR. 2834526 722.9xx 7/1 Capacity: 9 liter (Dry fill)		
USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		
Change every 60000 km		

MERCEDES-BENZ (EU) CLS-CLASS C219 CLS 300 219.354 (2009-2010)



HYDRAULIC BRAKE SYSTEM ABS Capacity: 1,4-2,25 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-S DOT 4	

Change every 24 months

POWER STEERING Capacity: 1 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Fluid 3013	

COOLING SYSTEM Capacity: 5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 11	Coolant SP 12 EVO	
Okana and 050000 km/ 400 manufika		•

Change every 250000 km/ 180 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.