

MERCEDES-BENZ (EU) E-CLASS W124 / V124 / S124 / C124 / A124 E 300 DIESEL 4MATIC (1992-1995)

**ENGINE** OM603.913

Capacity: 7,5 liter, Filter capacity: 1,5 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Bi-Turbo 20W-50*Check every 3000 km, change every 10000 km/ 12 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Emperol 5W-40

PRODUCT RECOMMENDATION 2

Emperol 10W-40

PRODUCT RECOMMENDATION 3

Bi-Turbo 15W-40*Check every 3000 km, change every 10000 km/ 12 months*

USE	CLIMATE
Severe	Mediterranean

PRODUCT RECOMMENDATION 1

Bi-Turbo 20W-50*Change every 5000 km/ 6 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Emperol 5W-40

PRODUCT RECOMMENDATION 2

Emperol 10W-40

PRODUCT RECOMMENDATION 3

Bi-Turbo 15W-40*Change every 5000 km/ 6 months***DIFFERENTIAL FRONT**

Capacity: 1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1071

PRODUCT RECOMMENDATION 2

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 3

Gearlube LS 80W-90*Check every 20000 km***DIFFERENTIAL REAR LIMITED SLIP**

Capacity: 1,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1071

PRODUCT RECOMMENDATION 2

Gearlube LS 80W-90*Check every 20000 km*

MERCEDES-BENZ (EU) E-CLASS W124 / V124 / S124 / C124 / A124 E 300 DIESEL 4MATIC (1992-1995)

**TRANSFERBOX**

Capacity: 0,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 4026	SP Matic 2032	

Check every 20000 km

TRANSMISSION AUTOMATIC 722.3xx 4/1

Capacity: 6,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 4026	SP Matic 2032	ATF Almirol

Check every 20000 km, change every 60000 km

TRANSMISSION MANUAL 5/1

Capacity: 1,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 4026	SP Matic 2032	ATF-A

Check every 20000 km

HYDRAULIC LEVELLING SYSTEM

Capacity: 2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3023		

Check every 20000 km

HYDRAULIC BRAKE/CLUTCH SYSTEM

Capacity: 0,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-S DOT 4		

Check every 20000 km, change every 12 months

PRODUCT RECOMMENDATION

MERCEDES-BENZ (EU) E-CLASS W124 / V124 / S124 / C124 / A124 E 300 DIESEL 4MATIC (1992-1995)

**POWER STEERING**

Capacity: 1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 4026	SP Matic 2032	

Check every 20000 km

GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
HT Q9 High Grade Grease	Labora Grease	

COOLING SYSTEM

Capacity: 9,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 11		

Check every 20000 km, change every 36 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.