

MERCEDES-BENZ (EU) E-CLASS W211 / S211 E 280 4MATIC 211.092/292 (2007-2009)



ENGINE M272.943/944
Capacity: 8 liter

USE	CLIMATE
Extended	Moderate

PRODUCT RECOMMENDATION 1

Helar 0W-40

Change every 25000 km/ 12 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Helar 0W-40

PRODUCT RECOMMENDATION 2

Emperol 5W-40

PRODUCT RECOMMENDATION 3

Emperol 5W-50

Change every 15000 km/ 12 months

DIFFERENTIAL FRONT
Capacity: 0,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1071

PRODUCT RECOMMENDATION 2

Gearlube LS 80W-90

DIFFERENTIAL REAR
Capacity: 1-1,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1071

PRODUCT RECOMMENDATION 2

Gearlube LS 80W-90

TRANSFERBOX

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032

Change every 60000 km

MERCEDES-BENZ (EU) E-CLASS W211 / S211 E 280 4MATIC 211.092/292 (2007-2009)

**TRANSMISSION AUTOMATIC** 722.6xx 5/1

Capacity: 9 liter

USE

First change only

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026*Change every 60000 km***HYDRAULIC BRAKE SYSTEM ABS**

Capacity: 1,4-2,25 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-S DOT 4*Change every 24 months***POWER STEERING**

Capacity: 1,1 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Fluid 3013**COOLING SYSTEM**

Capacity: 6,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 11

PRODUCT RECOMMENDATION 2

Coolant SP 12 EVO*Change every 250000 km/ 180 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.