

# MERCEDES-BENZ (EU) E-CLASS W211 / S211 E 300 BLUETEC 211.024 (2008-2009)



**ENGINE** OM642.920  
Capacity: 8,5 liter

| USE                         |                             | CLIMATE                   |
|-----------------------------|-----------------------------|---------------------------|
| Normal                      |                             | Moderate                  |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3  |
| <b>Helar SP LL-03 0W-30</b> | <b>Helar SP LL-03 5W-30</b> | <b>Presteza MSP 5W-30</b> |

*Change every 25000 km/ 12 months*

**DIFFERENTIAL REAR**  
Capacity: 1-1,6 liter

| USE                      |                           | CLIMATE  |
|--------------------------|---------------------------|----------|
| Normal                   |                           | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2  |          |
| <b>SP Gear 1071</b>      | <b>Gearlube LS 80W-90</b> |          |

**TRANSMISSION AUTOMATIC** 722.9xx 7/1  
Capacity: 9,7 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| First change only        |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>SP Matic 4026</b>     |  |          |

*Change every 60000 km*

**HYDRAULIC BRAKE SYSTEM ABS**  
Capacity: 1,4-2,25 liter

| USE                       |  | CLIMATE  |
|---------------------------|--|----------|
| Normal                    |  | Moderate |
| PRODUCT RECOMMENDATION 1  |  |          |
| <b>Drauliquid-S DOT 4</b> |  |          |

*Change every 24 months*

**POWER STEERING**  
Capacity: 1,1 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>SP Fluid 3013</b>     |  |          |

# MERCEDES-BENZ (EU) E-CLASS W211 / S211 E 300 BLUETEC 211.024 (2008-2009)



## COOLING SYSTEM

Capacity: 7,5 liter

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>Coolant SP 11</b>     | <b>Coolant SP 12 EVO</b> |          |

Change every 250000 km/ 180 months

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*