

MERCEDES-BENZ (EU) E-CLASS W211 / S211 E 350 4MATIC 211.087/287 (2007-2009)



ENGINE M272.972

USE	CLIMATE
Extended	Moderate

PRODUCT RECOMMENDATION 1

Helar 0W-40*Change every 25000 km/ 12 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Helar 0W-40

PRODUCT RECOMMENDATION 2

Emperol 5W-40

PRODUCT RECOMMENDATION 3

Emperol 5W-50*Change every 15000 km/ 12 months*

DIFFERENTIAL FRONT

Capacity: 0,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1071

PRODUCT RECOMMENDATION 2

Gearlube LS 80W-90

DIFFERENTIAL REAR

Capacity: 1-1,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1071

PRODUCT RECOMMENDATION 2

Gearlube LS 80W-90

TRANSFERBOX

Capacity: 0,59 liter

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032*Change every 60000 km*

MERCEDES-BENZ (EU) E-CLASS W211 / S211 E 350 4MATIC 211.087/287 (2007-2009)


TRANSMISSION AUTOMATIC 722.6xx 5/1

Capacity: 9,7 liter

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026

Change every 60000 km

HYDRAULIC BRAKE SYSTEM ABS

Capacity: 1,4-2,25 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-S DOT 4

Change every 24 months

POWER STEERING

Capacity: 1,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Fluid 3013
COOLING SYSTEM

Capacity: 10-10,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 11

PRODUCT RECOMMENDATION 2

Coolant SP 12 EVO

Change every 250000 km/ 180 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.