MERCEDES-BENZ (EU) E-CLASS W212 / V212 / S212 E 200 NGT BLUEEFFICIENCY 212.041 (2010-2013)



ENGINE M271.958 Capacity: 5,5 liter		
USE		CLIMATE
Extended drain (max)		Moderate
PRODUCT RECOMMENDATION 1		
Helar 0W-40		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30	Presteza MSP 5W-30

	CLIMATE
	Moderate
m	m

DIFFERENTIAL REAR 200 FE, Ø 200 mr Capacity: 1,1 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 1071	

DIFFERENTIAL REAR 215 FE, Ø 215 mr Capacity: 1,2 liter	1	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 1071		

MERCEDES-BENZ (EU) E-CLASS W212 / V212 / S212 E 200 NGT BLUEEFFICIENCY 212.041 (2010-2013)



	сымате Moderate
5/1	5/1

HYDRAULIC BRAKE SYSTEM Capacity: 0,6 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-S DOT 4	
Observes success 0.4 manufility	

Change every 24 months

POWER STEERING Capacity: 0,8 liter	
use Normal	сымате Moderate
PRODUCT RECOMMENDATION 1	
SP Fluid 3013	

COOLING SYSTEM Capacity: 0-0 liter (Between min and max.)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 11	Coolant SP 12 EVO	

Change every 250000 km/ 180 months

AIRCONDITIONING COMPRESSOR Capacity: 120 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM Capacity: 590 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.