MERCEDES-BENZ (EU) E-CLASS W212 / V212 / S212 E 280 4MATIC 212.081 (2009-2010)



ENGINE M272.950 Capacity: 7 liter		
USE		CLIMATE
		N.4 1
Flexible (max)		Moderate
FIEXIDIE (MAX) PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3

DIFFERENTIAL FRONT Capacity: 0,6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1071	Gearlube LS 80W-90	

DIFFERENTIAL REAR Capacity: 1-1,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1071	Gearlube LS 80W-90	

TRANSMISSION AUTOMATIC 722.9XX AS OF PRODUCTION NR. 2834527 722.9xx 7/1 Capacity: 9,7 liter (Dry fill)		
USE	CLIMATE	
Initial service	Moderate	
PRODUCT RECOMMENDATION 1		
SP Matic 2094		
Change every 50000 km/ 36 months		

TRANSMISSION AUTOMATIC 722.9XX UP TO PRODUCTION NR. 2834526 722.9xx 7/1 Capacity: 9,7 liter (Dry fill)		
USE	CLIMATE	
Initial service	Moderate	
PRODUCT RECOMMENDATION 1		
SP Matic 4026		
Change every 50000 km/ 36 months		

MERCEDES-BENZ (EU) E-CLASS W212 / V212 / S212 E 280 4MATIC 212.081 (2009-2010)



HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-S DOT 4	

Change every 24 months

POWER STEERING Capacity: 0,8 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Fluid 3013	

	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	
Coolant SP 12 EVO	

Change every 250000 km/ 180 months

AIRCONDITIONING COMPRESSOR Capacity: 120 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM Capacity: 590 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.