

# MERCEDES-BENZ (EU) G-CLASS W461 / 463 G 500 463.202/222/236/237 (2012-2015)



**ENGINE** M273.963, M273.969  
Capacity: 9 liter

USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Helar 0W-40</b>	<b>Emperol 5W-40</b>	<b>Emperol 5W-50</b>

**DIFFERENTIAL FRONT**  
Capacity: 1,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Gearlube GL-5 80W-90</b>		

*Change every 80000 km/ 48 months*

**DIFFERENTIAL FRONT LIMITED SLIP** 730.331  
Capacity: 1,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Gearlube Racing 75W-140</b>		

*Change every 80000 km/ 48 months*

**DIFFERENTIAL REAR**  
Capacity: 1,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Gearlube GL-5 80W-90</b>		

*Change every 80000 km/ 48 months*

**TRANSFERBOX** 750.654  
Capacity: 2,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Syngear HS 75W-90</b>		

*Change every 120000 km/ 48 months*

# MERCEDES-BENZ (EU) G-CLASS W461 / 463 G 500 463.202/222/236/237 (2012-2015)


**TRANSMISSION AUTOMATIC 722.9XX AS OF PRODUCTION NR. 2834527 722.9xx 7/1**

Capacity: 9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**SP Matic 2094***Change every 125000 km/ 60 months*
**TRANSMISSION AUTOMATIC 722.9XX UP TO PRODUCTION NR. 2834526 722.9xx 7/1**

Capacity: 9 liter

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1

**SP Matic 4026***Change every 60000 km*
**HYDRAULIC SYSTEM CONVERTIBLE ROOF**

Capacity: 0,24 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**SP Fluid 3023**
**HYDRAULIC SYSTEM DIFFERENTIAL LOCK**

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Drauliquid-S DOT 4***Change every 12 months*
**HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Drauliquid-S DOT 4***Change every 12 months*

# MERCEDES-BENZ (EU) G-CLASS W461 / 463 G 500 463.202/222/236/237 (2012-2015)

**POWER STEERING**

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>SP Matic 4026</b>	<b>SP Matic 2032</b>	

**COOLING SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant SP 11</b>	<b>Coolant SP 12 EVO</b>	

*Change every 250000 km/ 180 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*