

MERCEDES-BENZ (EU) G-CLASS W461 / 463 G 55 AMG KOMPRESSOR 463.270/271 (2009-2012)

**ENGINE** M113.993

Capacity: 8,5 liter (Service fill), Filter capacity: 0,5 liter

USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1		
Helar 0W-40		

DIFFERENTIAL FRONT 730.331

Capacity: 1,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube Racing 75W-140		

*Change every 80000 km/ 48 months***DIFFERENTIAL REAR LIMITED SLIP**

Capacity: 1,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube Racing 75W-140		

*Change every 80000 km/ 48 months***TRANSFERBOX** 750.654

Capacity: 2,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Syngear HS 75W-90		

*Change every 120000 km/ 48 months***TRANSMISSION AUTOMATIC** 722.630 5/1

Capacity: 8,6-9,1 liter

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		

Change every 60000 km

PRODUCT RECOMMENDATION

MERCEDES-BENZ (EU) G-CLASS W461 / 463 G 55 AMG KOMPRESSOR 463.270/271 (2009-2012)



TRANSMISSION AUTOMATIC 722.645 5/1

Capacity: 8,8-9,2 liter

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026

Change every 60000 km

HYDRAULIC SYSTEM CONVERTIBLE ROOF

Capacity: 0,24 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Fluid 3023

HYDRAULIC SYSTEM DIFFERENTIAL LOCK

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-S DOT 4

Change every 12 months

HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-S DOT 4

Change every 12 months

POWER STEERING

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026

PRODUCT RECOMMENDATION 2

SP Matic 2032

MERCEDES-BENZ (EU) G-CLASS W461 / 463 G 55 AMG KOMPRESSOR 463.270/271 (2009-2012)

**COOLING SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 11	Coolant SP 12 EVO	

Change every 250000 km/ 180 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.