## MERCEDES-BENZ (EU) M-CLASS W164 ML 350 4MATIC 164.186 (2007-2009)



| ENGINE M272.967<br>Capacity: 8 liter |                          |                          |
|--------------------------------------|--------------------------|--------------------------|
| USE                                  |                          | CLIMATE                  |
| Extended                             |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1             |                          |                          |
| Helar 0W-40                          |                          |                          |
| Change every 25000 km/ 12 months     |                          |                          |
| USE                                  |                          | CLIMATE                  |
| Normal                               |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1             | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Helar 0W-40                          | Emperol 5W-40            | Emperol 5W-50            |
| Change every 15000 km/ 12 months     | ·                        |                          |

| <b>DIFFERENTIAL FRONT</b> Capacity: 1,1 liter |                          |          |  |
|---|--------------------------|----------|--|
| USE   |                          | CLIMATE  |  |
| Normal  |                          | Moderate |  |
| PRODUCT RECOMMENDATION 1                      | PRODUCT RECOMMENDATION 2 |          |  |
| SP Gear 1071                                  | Gearlube LS 80W-90       |          |  |

| DIFFERENTIAL REAR Capacity: 1,1 liter |                          |          |  |
|---------------------------------------|--------------------------|----------|--|
| USE                                   |                          | CLIMATE  |  |
| Normal                                |                          | Moderate |  |
| PRODUCT RECOMMENDATION 1              | PRODUCT RECOMMENDATION 2 |          |  |
| SP Gear 1071                          | Gearlube LS 80W-90       |          |  |

| DIFFERENTIAL REAR DIFFERENTIAL LOCK Capacity: 1,6 liter |  |          |
|---|--|----------|
| USE   |  | CLIMATE  |
| Normal  |  | Moderate |
| PRODUCT RECOMMENDATION 1                                |  |          |
| SP Gear 1071  |  |          |
|   |  |          |

## MERCEDES-BENZ (EU) M-CLASS W164 ML 350 4MATIC 164.186 (2007-2009)



| TRANSFERBOX Capacity: 0,5 liter, Capacity: 1,5 liter (+ dual range) |            |  |
|---|------------|--|
|   | CLIMATE    |  |
|   | Moderate   |  |
|   |            |  |
|   |            |  |
| ı   | ual range) |  |

| TRANSMISSION AUTOMATIC 722.9xx 7 Capacity: 9 liter | /1 |          |
|--|----|----------|
| USE  |    | CLIMATE  |
| First change only                                  |    | Moderate |
| PRODUCT RECOMMENDATION 1                           |    |          |
| SP Matic 4026                                      |    |          |
| Change every 60000 km                              |    |          |

| HYDRAULIC BRAKE SYSTEM ABS<br>Capacity: 0,8 liter |          |
|---|----------|
| USE   | CLIMATE  |
| Normal  | Moderate |
| PRODUCT RECOMMENDATION 1                          |          |
| Drauliquid-S DOT 4                                |          |
| Change every 24 months                            | ·        |

| POWER STEERING Capacity: 1,2 liter |                          |          |
|------------------------------------|--------------------------|----------|
| USE                                |                          | CLIMATE  |
| Normal                             |                          | Moderate |
| PRODUCT RECOMMENDATION 1           | PRODUCT RECOMMENDATION 2 |          |
| SP Matic 4026                      | SP Matic 2032            |          |

| COOLING SYSTEM Capacity: 0-0 liter (Between min an | d max.)                  |          |
|--|--------------------------|----------|
| USE  |                          | CLIMATE  |
| Normal   |                          | Moderate |
| PRODUCT RECOMMENDATION 1                           | PRODUCT RECOMMENDATION 2 |          |
| Coolant SP 11                                      | Coolant SP 12 EVO        |          |
| Change every 250000 km/ 180 mod                    | nths                     | ,        |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the

information contained herein is subject to changes without notification.