MERCEDES-BENZ (EU) M-CLASS W166 ML 350 166.058 (2012-2015)



ENGINE M276.955 Capacity: 7 liter		
USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1		
Helar 0W-40		
Change every 15000 km		
DIFFERENTIAL REAR 187 FE, Ø 187 mr Capacity: 0,95 liter	n	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 1071		
DIFFERENTIAL REAR 200 FE, Ø 200 mr	n	
Capacity: 1,1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 1071		
DIFFERENTIAL REAR 215 FE, Ø 215 mr	~	
Capacity: 1,2 liter	"	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 1071		
TRANSMISSION AUTOMATIC 722.9xx 7	//4	
Capacity: 9 liter (Dry fill)	/ 1	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2094		
Change every 125000 km/ 60 months	-	

MERCEDES-BENZ (EU) M-CLASS W166 ML 350 166.058 (2012-2015)



ACTIVE CURVE SYSTEM Capacity: 2 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Fluid 3013	

HYDRAULIC BRAKE SYSTEM ABS Capacity: 0,8 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-S DOT 4	
Change every 24 months	·

COOLING SYSTEM Capacity: 10,5 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant SP 11	Coolant SP 12 EVO		
Change 2427, 250000 km/ 100 ma	ntho	•	

Change every 250000 km/ 180 months

AIRCONDITIONING COMPRESSOR

Capacity: 120 CM3, Capacity: 160 CM3 (+ code 582)

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM

Capacity: 1050 grams, Capacity: 1400 grams (+ code 582)

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.